

2GE

G 铣刀 2 刃型
G End Mills Standard Two Flutes

切削条件 Milling Condition / C-204

HSS Co
工具材料

G
涂层


30°
~35°
螺旋角

h7
标准段公差

1-50
外径范围

●可用于从普通钢到不锈钢以及铝的泛用涂层立铣刀。

This is general coated end mill for grooving.



LIST 6272P

订货方式

2GE 外径 带*标记商品的订货方式 2GE 外径 X 长度

单位 (Unit) : mm

外径 Dc	刃长 ℓ	全长 L	柄直径 Ds	库存 Stock
1	2	50	6	●
1.1	2.5			
1.2				
1.3	3			
1.4				
1.5				
1.6	3.5			
1.7				
1.8	4			
1.9				
2				
2.1	4.5			
2.2				
2.3	5			
2.4				
2.5	5.5			
2.6				
2.7	6			
2.8				
2.9	6.5			
3				
3.1	7			
3.2				
3.3	8			
3.4				
3.5	60	8	●	
3.6				
3.7				
3.8				
3.9				
4				
4.1				9
4.2				
4.3				10
4.4				
4.5				
4.6				
4.7				
4.8				
4.9				
5	12			
5.1				
5.2				
5.3				
5.4				
5.5				
5.6				
5.7				
5.8				
5.9				
6	65	10	●	
6.1				
6.2				
6.3				
6.4				
6.5				
6.6				
6.7				
6.8				
6.9				
7				
7.1				
7.2				
7.3				
7.4				
7.5				

外径 Dc	刃长 ℓ	全长 L	柄直径 Ds	库存 Stock
7.6	14	65	10	●
7.7				
7.8				
7.9				
8				
8.1				
8.2				
8.3				
8.4				
8.5				
8.6	70			
8.7				
8.8				
8.9				
9				
9.1				
9.2				
9.3				
9.4				
9.5				
9.6	80			
9.7				
9.8				
9.9				
10				
10.1				
10.2				
10.3				
10.4				
10.5				
10.6				
10.7				
10.8				
10.9				
11	90			
11.1				
11.2				
11.3				
11.4				
11.5				
11.6				
11.7				
11.8				
11.9				
12	95			
12.1				
12.2				
12.3				
12.4				
12.5				
12.6				
12.7				
12.8				
12.9				
13	105			
13.5				
14				
14.5				
15				
15.5				
16				
16.5				
17				
17.5				
18	20			
18.5				
40	110			

●为标准库存品。
Standard stock item.

- G
- 刀头
- 平头型
- 圆角型
- 球头型
- 刃数
- 2刃型
- 3刃型
- 4刃型
- 6刃型~
- 长刃
- 长颈长柄
- 粗加工、半精加工
- 铝、有色金属