

4GE

G 铣刀 4 刃型

G End Mills Standard Four Flutes

切削条件 Milling Condition ▶▶▶ C-208

HSS Co
工具材料

G
涂层


30°
螺旋角

h7
轴直径公差

2.5-50
外径范围

- 可用于从普通钢到不锈钢以及铝的泛用涂层立铣刀。适用于侧面加工。

This is general coated end mill for side milling.



LIST 6274P

订货方式

4GE 外径 带 * 标记商品的订货方式 4GE 外径 × 长度

单位 (Unit) : mm

外径 Dc	刃长 ℓ	全长 L	柄直径 Ds	库存 Stock
2.5	7	50	6	
3	9			
3.5	12			
4	15	60	8	
4.5				
5				
5.5	20	65	10	
6				
6.5				
7	25	75	12	
7.5				
8				
8.5	30	80	16	
9				
9.5				
10	35	90	20	
10.5				
11				
11.5	40	105	25	
12				
12.5				
13	45	110	32	
13.5				
14				
14.5	50	120	42	
15				
15.5				
16	55	125	42	
16.5				
17				
17.5	60	145	32	
18				
18.5				
19	65	150	42	
19.5				
20				
21	70	155	32	
22				
23				
24	70	160	42	
25				
26				
27	70	160	42	
28				
29				
30	70	160	42	
31				
32				
33	70	160	42	
34				
35				
36	70	160	42	
37				
38				
39	70	160	42	
40				
42				
* 42	70	160	42	
45				
* 45				

外径 Dc	刃长 ℓ	全长 L	柄直径 Ds	库存 Stock
48	70	155	32	●
* 48		160	42	
50		155	32	
* 50		160	42	

外径 (mm) Dc		公差 (mm) Tolerance
超过 Above	以下 Up to	
	10	+0.020 ~ 0
10	30	+0.025 ~ 0
30		+0.030 ~ 0

一般结构用钢	碳钢	合金钢	预硬钢	调质钢 模具钢	高硬度钢	
SS400	S45C S50C	SCM SCR	NAK	30~45HRC	45~55HRC	55~60HRC
○	○	○	○	○	×	×
高硬度钢	不锈钢	钛合金 耐热合金	铸铁	铝合金	铜合金	石墨
60~65HRC	SUS304 SUS316	SUS420	FCD FC	AC/ADC	Cu	Graphite
×	○	○	○	○	○	

○:最佳 Excellent ○:适用 Good ×:不适用 Not Used 无标记 (No mark) 不推荐 Not recommended