


●适用于从新材到淬火材料的多种材料。适用于精加工。

This end mill is suitable for workpiece materials from raw materials to hardened materials, and for finish milling.



LIST 9382

订货方式

商品编码

商品编码 CODE	外径 Dc	刃长 l	全长 L	柄直径 Ds	库存 Stock
2GS0.2	0.2	0.4	40	4	●
2GS0.3	0.3	0.6			
2GS0.4	0.4	0.8			
2GS0.5 × 4	0.5	1.25			
2GS0.6	0.6	1.5			
2GS0.7	0.7	2			
2GS0.8	0.8	2			
2GS0.9	0.9	2			
2GS1 × 4	1	2.5			
2GS1.1	1.1	2.5			
2GS1.2	1.2	3			
2GS1.3	1.3	3			
2GS1.4	1.4	3			
2GS1.5 × 4	1.5	3.75			
2GS1.6	1.6	4			
2GS1.7	1.7	4			
2GS1.8	1.8	5			
2GS1.9	1.9	5			
2GS2 × 4	2	6			
2GS2.1	2.1	6			
2GS2.2	2.2	6			
2GS2.3	2.3	6			
2GS2.4	2.4	6			
2GS2.5 × 4	2.5	6.25			
2GS2.6	2.6	7			
2GS2.7	2.7	7			
2GS2.8	2.8	7			
2GS2.9	2.9	7			
2GS3 × 6	3	7.5			
2GS3.1	3.1	8			
2GS3.2	3.2	8			
2GS3.3	3.3	8			
2GS3.4	3.4	10			
2GS3.5	3.5	10			
2GS3.6	3.6	10			
2GS3.7	3.7	10			
2GS3.8	3.8	10			
2GS3.9	3.9	10			
2GS4 × 6	4	11			
2GS4.1	4.1	11			
2GS4.2	4.2	11			
2GS4.3	4.3	11			
2GS4.4	4.4	11			
2GS4.5	4.5	11			
2GS4.6	4.6	11			
2GS4.7	4.7	11			
2GS4.8	4.8	11			
2GS4.9	4.9	11			
2GS5	5	13			
2GS5.1	5.1	13			
2GS5.2	5.2	13			
2GS5.3	5.3	13			
2GS5.4	5.4	13			
2GS5.5	5.5	13			
2GS5.6	5.6	13			
2GS5.7	5.7	13			
2GS5.8	5.8	13			
2GS5.9	5.9	13			
2GS6	6	16			
2GS7 × 8	7	16			
2GS8	8	19			
2GS9 × 10	9	22			
2GS10	10	22			
2GS11 × 12	11	26			
2GS12	12	26			
2GS13	13	26			
2GS14	14	26			
2GS15	15	26			
2GS16	16	32			
2GS18	18	32			
2GS20	20	38			

单位 (Unit) : mm

商品编码 CODE	外径 Dc	刃长 l	全长 L	柄直径 Ds	库存 Stock
2GS8	8	19	60	8	●
2GS9 × 10	9	22	70	10	
2GS10	10	22	70	10	
2GS11 × 12	11	26	75	12	
2GS12	12	26	75	12	
2GS13	13	26	75	12	
2GS14	14	26	75	12	
2GS15	15	26	75	12	
2GS16	16	32	90	16	
2GS18	18	32	90	16	
2GS20	20	38	100	20	

单位 (Unit) : mm

商品编码 CODE	外径 Dc	刃长 l	全长 L	柄直径 Ds	库存 Stock			
2GS0.5	0.5	1.25	38	3	●			
2GS1	1	2.5						
2GS1.5	1.5	3.75						
2GS2	2	5						
2GS2.5	2.5	6.25						
2GS3	3	7.5						
2GS4	4	11						
2GS0.5	0.5	1.25				45	4	●
2GS1	1	2.5						
2GS1.5	1.5	3.75						
2GS2	2	5						
2GS2.5	2.5	6.25						
2GS3	3	7.5						
2GS4	4	11						

外径 (mm) Dc		公差 (mm) Tolerance
超过 Above	以下 Up to	
	3	0 ~ -0.015
3	12	0 ~ -0.020
12		0 ~ -0.030

一般 结构用钢	碳钢	合金钢	预硬钢	调质钢 模具钢	高硬度钢	
SS400	S45C S50C	SCM SCR	NAK	30-45HRC	45-55HRC 55-60HRC	
○	○	○	○	○	○	
高硬度钢	不锈钢	钛合金 耐热合金	铸铁	铝合金	铜合金	石墨
60-65HRC	SUS304 SUS316	SUS420	FCD FC	AC/ADC	Cu	Graphite
○	○	○	○	○	○	○

○:最佳 Excellent ○:适用 Good ×:不适用 Not Used 无标记 (No mark):不推荐 Not recommended

锋利型刀尖, 适用于精加工。标记的说明请参照 49 页。